

# VISION 570™/560™

Advanced PLC from the back-big & beautiful color 5.7" touchscreen from the front. Snap-in I/Os for an All-in-One; expand up to 1000 I/Os

## Features:

### HMI

- Up to 1024 user-designed screens
- 500 images per application
- HMI graphs - color-code Trends
- Built-in alarm screens
- Text String Library - easy localization
- Memory and communication monitoring via HMI - No PC needed

### PLC

- I/O options include high-speed, temperature & weight measurement
- Auto-tune PID, up to 24 independent loops
- Recipe programs and datalogging via Data Tables
- SD card - log, backup, clone & more
- Date & Time-based control

### Communication

- TCP/IP via Ethernet
- Web server: Use built-in HTML pages, or design complex pages to view and edit PLC data via the Internet
- Send e-mail function
- SMS messaging
- GPRS/GSM
- Remote Access utilities
- MODBUS protocol support
- CANbus: CANopen, UniCAN, SAE J1939 and more
- DF1 Slave
- SNMP Agent V1
- FB Protocol Utility: enables serial or TCP/IP communications with 3<sup>rd</sup>-party device; barcode readers, frequency converters, etc
- Ports: supplied with 2 isolated RS232/RS485 and 1 CANbus; In Vision570: 1 USB programming port; 1 port may be added for serial/Ethernet

### V560



### V570

Classic Panel



### V570-J

Flat Panel

“

For a first time user, I had a great experience. I look forward to incorporating this brand of product on future jobs. ”

CE/UL

Jeremy Charles Keene,  
Controls Manager at General Broach Company

	<b>V570</b>		<b>V560</b>
Article Number	<b>V570-57-T20B</b>	<b>V570-57-T20B-J</b>	<b>V560-T25B*</b>
<b>I/O Options</b>	Plug these modules directly into the back of the Vision unit to create a self-contained PLC with up to 62 I/Os. Inputs may include Digital, Analog, and Temperature measurement. Outputs may include Transistor, Relay, or Analog. (sold separately)		
Snap-in I/O Modules			
I/O Expansion	Local or Remote I/Os may be added via expansion port or via CANbus		
<b>Program</b>			
Application Memory	Application Logic: 2MB • Images: 12MB for V570, 6MB for V560 • Fonts: 1MB		
Scan Time	9µsec per 1K of typical application		
Memory Operands	8192 coils, 4096 registers, 512 long integers (32-bit), 256 double words (32-bit unsigned), 64 floats, 384 timers (32-bit), 32 counters. Additional non-retainable operands: 1024 X-bits, 512 X-integers, 256 X-long integers, 64 X-double words		
Data Tables	120K dynamic RAM data (recipe parameters, datalogs, etc.), up to 256K fixed data		
SD Card	Store datalogs, Alarm History, Data Tables, Trend data, export to Excel • Back up Ladder, HMI & OS, clone PLCs		
Enhanced Features	Trends: graph any value and display on HMI • Built-in Alarm management system • String Library: instantly switch HMI language		
<b>Operator Panel</b>			
Type	TFT LCD		
Display Backlight Illumination	White LED		
Colors	65,536 colors, 16 bit resolution • Brightness - Adjustable via touchscreen or software		
Display Resolution & Size	320 x 240 pixels (QVGA), 5.7"		
Touchscreen	Resistive, Analog		
Keys	Virtual keyboard	24 programmable keys. Labeling options – function keys or customized	
<b>General</b>			
Power Supply	12/24VDC		
Battery	7 years typical at 25°C, battery back-up for all memory sections and RTC		
Clock	Real-time clock functions (date and time)		
Environment	IP65/NEMA4X (when panel mounted)	IP66/IP65/NEMA4X (when panel mounted)	IP65/NEMA4X (when panel mounted)
Standard	CE, UL Many of our products are also UL Class 1 Div 2 and GOST certified - please contact Unitronics		

\* Not yet UL certified

This guide provides specifications for Unitronics' controller V560-T25B, which comprises a built-in operating panel containing a 5.7" color touchscreen and an alpha-numeric keypad with function keys. You can find additional documentation on the Unitronics' Setup CD and in the Technical Library at [www.unitronics.com](http://www.unitronics.com).

## Technical Specifications

---

### **Power Supply**

Input voltage	12 or 24VDC
Permissible range	10.2-28.8VDC
Max. current consumption	540mA@12V 270mA@24V

---

### **Battery**

Back-up	7 years typical at 25°C, battery back-up for RTC and system data, including variable data.
Replaceable	Yes, without opening the controller.

---

### **Graphic Display Screen**

	See Note 1
LCD Type	TFT
Illumination backlight	White LED
Display resolution, pixels	320x240 (QVGA)
Viewing area	5.7"
Colors	65,536 (16-bit)
Touchscreen	Resistive, analog
'Touch' indication	Via buzzer
Screen brightness	Via software (Store value to SI 9).
Keypad	Displays virtual keyboard when the application requires data entry.

### **Notes:**

1. Note that the LCD screen may have a single pixel that is permanently either black or white.
- 

### **Keypad**

Number of keys	24 programmable function keys
Key type	Metal dome, sealed membrane switch
Slides	Slides may be installed in the operating panel faceplate to custom-label the keys. One blank set of slides is supplied with the controller.

## **Program**

Memory size Application Logic – 2MB, Images – 6MB, Fonts – 1MB

Operand type	Quantity	Symbol	Value
Memory Bits	8192	MB	Bit (coil)
Memory Integers	4096	MI	16-bit
Long Integers	512	ML	32-bit
Double Word	256	DW	32-bit unsigned
Memory Floats	64	MF	32-bit
Timers	384	T	32-bit
Counters	32	C	16-bit

Data Tables 120K dynamic data (recipe parameters, datalogs, etc.)  
192K fixed data (read-only data, ingredient names, etc)

HMI displays Up to 1024

Program scan time 9 µsec per 1K of typical application

## **Removable Memory**

SD card Compatible with fast SD cards; store datalogs, Alarms, Trends, Data Tables, backup Ladder, HMI, and OS. See Note 2

## **Notes:**

2. User must format via Unitronics SD tools utility.

## **Communication**

Serial ports 2. See Note 3

### RS232

Galvanic isolation Yes  
Voltage limits ±20VDC absolute maximum  
Baud rate range 300 to 115200 bps  
Cable length Up to 15m (50')

### RS485

Galvanic isolation Yes  
Voltage limits –7 to +12VDC differential maximum  
Baud rate range 300 to 115200 bps  
Nodes Up to 32  
Cable type Shielded twisted pair, in compliance with EIA RS485  
Cable length 1200m maximum (4000')

### CANbus port

Nodes

CANopen	Unitronics' CANbus protocols
127	60

Power requirements 24VDC (±4%), 40mA max. per unit. See Note 4

Galvanic isolation Yes, between CANbus and controller

Cable length/baud rate

25 m	1 Mbit/s
100 m	500 Kbit/s
250 m	250 Kbit/s
500 m	125 Kbit/s
500 m	100 Kbit/s
1000 m*	50 Kbit/s
1000 m*	20 Kbit/s

\* If you require cable lengths over 500 meters, contact technical support.

Optional port                                      User may install a single Ethernet port, or an RS232/RS485 port.  
Available by separate order.

**Notes:**

3. The standard for each port is set to either RS232/RS485 according to DIP switch settings. Refer to the Installation Guide.
4. Supports both 12 and 24VDC CANbus power supply, (±4%), 40mA maximum per unit. Note that if 12 VDC is used, the maximum cable length is 150 meters.

---

**I/Os**

	Number of I/Os and types vary according to module. Supports up to 1024 digital, high-speed, and analog I/Os.
Snap-in I/O modules	Plugs into rear port to create self-contained PLC with up to 62 I/Os.
Expansion modules	<u>Local adapter</u> (P.N. EX-A1), via I/O Expansion Port. Integrate up to 8 I/O Expansion Modules comprising up to 128 additional I/Os. <u>Remote adapter</u> (P.N. EX-RC1), via CANbus port. Connect up to 60 adapters; connect up to 8 I/O expansion modules to each adapter.
Exp. port isolation	Galvanic

**Dimensions**

Size	228.4X146.5X70.5mm (8.99"X5.76"X2.77"). See Note 5
Weight	750 gm (26.4 oz)

**Notes:**

5. For exact dimensions, refer to the product's Installation Guide.

---

**Mounting**

Panel-mounting	Via brackets
----------------	--------------

---

**Environment**

Inside cabinet	IP20 / NEMA1 (case)
Panel mounted	IP65 / NEMA4X (front panel)
Operational temperature	0 to 50°C (32 to 122°F)
Storage temperature	-20 to 60°C (-4 to 140°F)
Relative Humidity (RH)	5% to 95% (non-condensing)

The information in this document reflects products at the date of printing. Unitronics reserves the right, subject to all applicable laws, at any time, at its sole discretion, and without notice, to discontinue or change the features, designs, materials and other specifications of its products, and to either permanently or temporarily withdraw any of the foregoing from the market.

All information in this document is provided "as is" without warranty of any kind, either expressed or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement. Unitronics assumes no responsibility for errors or omissions in the information presented in this document. In no event shall Unitronics be liable for any special, incidental, indirect or consequential damages of any kind, or any damages whatsoever arising out of or in connection with the use or performance of this information.

The tradenames, trademarks, logos and service marks presented in this document, including their design, are the property of Unitronics (1989) (R"G) Ltd. or other third parties and you are not permitted to use them without the prior written consent of Unitronics or such third party as may own them.

DTS-V560-T25B 08/10