

# PLC + HMI ALL IN ONE™

**spectra**  
Industrie-PC & Automation



## SAMBA™

All-in-One SPS mit High-Resolution Farb-Touchscreen & onboard E/A-Konfiguration. Hohe Leistung zum kleinen Preis.

### Merkmale:

#### HMI

- Display: Farb-Touchscreen  
3.5" – 320 x 240 | 4.3" – 480 x 272 | 7" – 800 x 480
- 24 benutzerdefinierbare Displays und 40 Bilder pro Applikation
- Farbige Prozessbilder und Trendgrafiken
- Eingebaute Alarmdisplays
- Textbibliothek – einfache Sprachanpassung für mehrsprachige Applikationen
- Fehlerdiagnose via HMI Panel – kein PC nötig

#### SPS

- E/A-Optionen: digital, analog, inkl. High-Speed
- Auto-tune PID, 2 unabhängige Regelkreise
- Tabellen für Rezepte und Datenlogger
- Zeitbasierte Steuerung

#### Kommunikation

- TCP/IP via Ethernet
- SMS, E-Mail
- GPRS/GSM
- Fernzugriff über Modem
- Unterstützt MODBUS Protokoll
- BACnet, M-bus – via 3rd-party Konverter
- CANbus: CANopen, UniCAN, SAE J1939, ...
- DF1 Slave
- Ports: RS-232 Programmierport für 3.5", USB für 4.3" & 7" Modell
- Erweiterungsmöglichkeit um 2 Ports:  
1 x seriell (RS-232/RS-485) / Ethernet & 1 CANbus

MODELL		SAMBA							
		SM35-J-R20	Art. Nr. 132422	SM35-J-RA22	Art. Nr. 147880	SM35-J-T20	Art. Nr. 132423	SM35-J-TA22	Art. Nr. 148167
		SM43-J-R20	Art. Nr. 141764	SM43-J-RA22	Art. Nr. 147900	SM43-J-T20	Art. Nr. 141763	SM43-J-TA22	Art. Nr. 148171
		SM70-J-R20	Art. Nr. 143790	SM70-J-RA22	Art. Nr. 148161	SM70-J-T20	Art. Nr. 143791	SM70-J-TA22	Art. Nr. 148162
		10 digitale Eingänge 2 analoge / digitale Eingänge <sup>1</sup> 8 Relais-Ausgänge		8 digitale Eingänge 2 analoge / digitale Eingänge 2 Pt100 / TC / digitale Eingänge 8 Relais-Ausgänge 2 analoge Ausgänge		10 digitale Eingänge 2 analoge / digitale Eingänge 8 Transistor-Ausgänge		8 digitale Eingänge 2 analoge / digitale Eingänge 2 Pt100 / TC / digitale Eingänge 8 Transistor-Ausgänge 2 analoge Ausgänge	
EINGÄNGE									
Digital		12		12		12		12	
HSC/Shaft-Encoder/Max. Freq. <sup>2,3</sup>		1x 32-bit 30 kHz		1x 32-bit 30 kHz		3x 32-bit 30 kHz		1x 32-bit 30 kHz	
Analog		2x 0-10 V oder 0-20 mA, 4-20 mA 10-bit		2x 0-10 V oder 0-20 mA, 4-20 mA 2 Modi: Normal: 14-bit, Fast: 12-bit		2x 10-bit, 0-10 V 0-20 mA, 4-20 mA		2x 0-10 V oder 0-20 mA, 4-20 mA 2 Modi: Normal: 14-bit, Fast: 12-bit	
Temperatureingänge		-		und als 2x Pt100/TC		-		und als 2x Pt100/TC	
AUSGÄNGE									
Digital		8 Relais		8 Relais		8 npn		8 npn	
High-Speed Ausgänge/PWM		-		-		Ausgänge 0 bis 6 können als PWM Ausgang 0,5 kHz genutzt werden		Ausgänge 0 bis 4 können als PWM Ausgang 0,5 kHz genutzt werden	
Analog		-		2x 12-bit, 0-10 V, 4-20 mA		-		2x 12-bit, 0-10 V, 4-20 mA	
E/A-Erweiterung									
					Remote E/As via CANbus				
PROGRAMM									
Application Memory	SM35	Anwendungslogik: 112 kb, Bilder: 1 MB, Schriften: 512 k							
	SM43	Anwendungslogik: 112 kb, Bilder: 2 MB, Schriften: 512 k							
	SM70	Anwendungslogik: 112 kb, Bilder: 5 MB, Schriften: 512 k							
Zykluszeit	15µs per 1K für typ. Anwendung								
Speicheroperanden	512 coils, 256 registers, 32 long integers (32-bit), 32 double words (32-bit unsigned), 24 floats, 32 timer (32-bit), 16 counter. Zusätzliche flüchtige Operanden: 64 X-bits, 32 X-integers, 16 X-long integers, 16 X-double words								
Tabellen	32 k dynamische RAM Daten (Rezeptparameter, Datalogging, etc.), bis zu 16 k Flash Daten								
SD Card (Micro)	-								
Erweiterte Funktionen	Trends: Liniengrafik für alle Werte und Anzeige auf Display, Textbibliothek: einfache Sprachumschaltung								
BEDIENFELD									
Art & Farbe	TFT LCD • 65.536 Farben • 16-bit Auflösung • Helligkeit einstellbar via Touchscreen oder Software								
Display	SM35	Auflösung: 320 x 240 Pixel • Größe: 3.5" (QVGA)							
	SM43	Auflösung: 480 x 272 Pixel • Größe: 4.3"							
	SM70	Auflösung: 800 x 480 Pixel • Größe: 7"							
Touchscreen	resistiv, analog								
Tastatur	Anzeige der virtuellen Tastatur, wenn die Anwendung Dateneingabe benötigt								
ALLGEMEINES									
Stromversorgung	24 VDC								
Batterie	Stützbatterie für RTC und Systemdaten, inkl. variabler Daten, 7 Jahre typ. bei 25°C								
Uhr	Echtzeituhr-Funktionen (Datum und Zeit)								
Schutzart	NEMA4X / IP66 / IP65 (bei Schalttafelmontage)								
Zertifizierung	CE, UL								

1. Wenn die digitalen Eingänge als npn genutzt werden, steht die Analogoption nicht zur Verfügung.

2. Bestimmte Eingänge können als High-Speed Zähler, Shaft-Encoder Eingang oder als normaler digitaler Eingang genutzt werden.

3. Diese Spezifikation hängt von der Kabellänge ab.

# Samba™OPLC™

**SM35-J-R20 Art. Nr. 132422**  
**SM43-J-R20 Art. Nr. 141764**  
**SM70-J-R20 Art. Nr. 143790**  
**Technical Specifications**

## Ordering Information

### Item

SM35-J-R20	PLC with Flat panel, Color touch display 3.5"
SM43-J-R20	PLC with Flat panel, Color touch display 4.3"
SM70-J-R20	PLC with Flat panel, Color touch display 7"

You can find additional information, such as wiring diagrams, in the product's installation guide located in the Technical Library at [www.unitronics.com](http://www.unitronics.com).

## Power Supply

Item	SM35-J-R20	SM43-J-R20	SM70-J-R20
Input voltage	24VDC		
Permissible range	20.4VDC to 28.8VDC with less than 10% ripple		
Max. current consumption	See Note 1		
npn inputs	235mA@24VDC	235mA@24VDC	285mA@24VDC
pnp inputs	195mA@24VDC	195mA@24VDC	240mA@24VDC

### Notes:

- To calculate the actual power consumption, subtract the current for each unused element from the maximum current consumption value according to the values below:

	Backlight	Ethernet card	Relay Outputs (per output)
SM35/SM43	20mA	35mA	5mA
SM70	80mA	35mA	5mA

## Digital Inputs

Number of inputs	12. See Note 2
Input type	See Note 2
Galvanic isolation	None
Nominal input voltage	24VDC
Input voltage	
pnp (source)	0-5VDC for Logic '0' 17-28.8VDC for Logic '1'
npn (sink)	17-28.8VDC for Logic '0' 0-5VDC for Logic '1'
Input current	3.7mA@24VDC
Input impedance	6.5KΩ
Response time	10ms typical, when used as normal digital inputs
Input cable length	
Normal digital input	Up to 100 meters
High Speed Input	Up to 50 meters, shielded, see Frequency table below

## High speed inputs

Specifications below apply when wired as HSC/shaft-encoder.

See Note 2

See Note 3

Frequency (max)	Cable length (max.)	HSC	Shaft-encoder pnp	Shaft-encoder npn
	10m	30kHz	20kHz	16kHz
	25m	25kHz	12kHz	10kHz
	50m	15kHz	7kHz	5kHz
Duty cycle		40-60%		
Resolution		32-bit		

### Notes:

2. This model comprises a total of 12 inputs. Input functionality can be adapted as follows.

All 12 inputs may be used as digital inputs. They may be wired in a group via a single jumper as either npn or pnp.

In addition, according to jumper settings and appropriate wiring:

- Inputs 5 and 6 can function as either digital or analog inputs.
  - If the digital inputs function as npn, analog option is not available.
- Input 0 can function as a high-speed counter, as part of a shaft-encoder, or as normal digital inputs.
- Input 1 can function as either counter reset, normal digital input, or as part of a shaft-encoder.
- If input 0 is set as a high-speed counter (without reset), input 1 can function as a normal digital input.

3. pnp/npn maximum frequency is at 24VDC.

### Analog Inputs

Number of inputs	2, according to wiring as described above in Note 2	
Input type	Multi-range inputs: 0-10V, 0-20mA, 4-20mA	
Input range	0-20mA, 4-20mA	0-10VDC
Input impedance	243Ω	>150KΩ
Maximum input rating	25mA, 6V	15V
Galvanic isolation	None	
Conversion method	Successive approximation	
Resolution (except 4-20mA)	10-bit (1024 units)	
Resolution (at 4-20mA)	204 to 1023 (820 units)	
Conversion time	One configured input is updated per scan. See Note 4	
Precision	0.9%	
Status indication	Yes – if an analog input deviates above the permissible range, its value will be 1024.	

### Note:

4. For example, if 2 inputs are configured as analog, it takes 2 scans to update all analog values.

---

## Digital Outputs

Number of outputs	8 relay (in 2 groups). See Note 5
Output type	SPST-NO (Form A)
Isolation	By relay
Type of relay	Tyco PCN-124D3MHZ or compatible
Output current (resistive load)	3A maximum per output 8A maximum total per common
Rated voltage	250VAC / 30VDC
Minimum load	1mA, 5VDC
Life expectancy	100k operations at maximum load
Response time	10ms (typical)
Contact protection	External precautions required (see <i>Increasing Contact Life Span</i> in the product's Installation Guide)

### Note:

5. Outputs 0, 1, 2 and 3 share a common signal. Outputs 4, 5, 6, and 7 share a common signal.

---

## Graphic Display Screen

Item	SM35-J-R20	SM43-J-R20	SM70-J-R20
LCD Type	TFT, LCD display	TFT, LCD display	TFT, LCD display
Illumination backlight	White LED	White LED	White LED
Display resolution	320x240 pixels	480x272 pixels	800x480 pixels
Viewing area	3.5"	4.3"	7"
Colors	65,536 (16-bit)	65,536 (16-bit)	65,536 (16-bit)
Touchscreen	Resistive, analog	Resistive, analog	Resistive, analog
Screen brightness control	Via software (Store value to SI 9, values range: 0 to 100%)		
Virtual Keypad	Displays virtual keyboard when the application requires data entry.		

---

## Program

Item	SM35-J-R20	SM43-J-R20	SM70-J-R20
Memory size			
Application Logic	112KB	112KB	112KB
Images	1MB	2MB	5MB
Fonts	512KB	512KB	512KB
Operand type	Quantity	Symbol	Value
Memory Bits	512	MB	Bit (coil)
Memory Integers	256	MI	16-bit signed/unsigned
Long Integers	32	ML	32-bit signed/unsigned
Double Word	32	DW	32-bit unsigned
Memory Floats	24	MF	32-bit signed/unsigned
Fast Bits	64	XB	Fast Bits (coil) – not retained
Fast Integers	32	XI	16 bit signed/unsigned (fast, not retained)
Fast Long Integers	16	XL	32 bit signed/unsigned (fast, not retained)
Fast Double Word	16	XDW	32 bit unsigned (fast, not retained)
Timers	32	T	Res. 10 ms; max 99h, 59 min, 59.99s
Counters	16	C	32-bit
Data Tables	32K dynamic data (recipe parameters, datalogs, etc.) 16K fixed data (read-only data, ingredient names, etc)		
HMI displays	Up to 24		
Program scan time	15µs per 1kb of typical application		

---

## Communication Ports

Port 1	1 channel, RS232 (SM35) , USB device (SM43/SM70)
Galvanic isolation	SM35 and SM43 – No SM70 - Yes
Baud rate	300 to 115200 bps
<b>RS232 (SM35 only)</b>	
Input voltage	±20VDC absolute maximum
Cable length	15m maximum (50')
<b>USB device (SM43,SM70 only)</b>	
Port type	Mini-B
Specification	USB 2.0 complaint; full speed
Cable	USB 2.0 complaint; up to 3m
Port 2 (optional)	See Note 6
CANbus (optional)	See Note 6

### Notes:

6. The user may order and install one or both of the following modules:
- A serial RS232/RS485 isolated/non-isolated interface module, or an Ethernet Interface module in port 2.
  - A CANbus module
- modules documentation is available on the Unitronics website.

---

## Miscellaneous

Clock (RTC)	Real-time clock functions (date and time)
Battery back-up	7 years typical at 25°C, battery back-up for RTC and system data, including variable data
Battery replacement	Yes. Coin-type 3V, lithium battery, CR2450

---

## Dimensions

Item	SM35-J-R20	SM43-J-R20	SM70-J-R20
Size	109 x 114.1 x 68mm (4.29 x 4.49 x 2.67"). See Note 7	136 x 105.1 x 61.3mm (5.35 x 4.13 x 2.41"). See Note 7	210 x 146.4 x 42.3mm (8.26 x 5.76 x 1.66"). See Note 7
Weight	210g (7.4 oz)	350g (12.34 oz)	640g (22.57 oz)

### Notes:

7. For exact dimensions, refer to the product's Installation Guide.

---

## Environment

Operational temperature	0 to 50°C (32 to 122°F)
Storage temperature	-20 to 60°C (-4 to 140°F)
Relative Humidity (RH)	10% to 95% (non-condensing)
Mounting method	Panel mounted (IP65/66/NEMA4X) DIN-rail mounted (IP20/NEMA1)
Operating Altitude	2000m (6562 ft)
Shock	IEC 60068-2-27, 15G, 11ms duration
Vibration	IEC 60068-2-6, 5Hz to 8.4Hz, 3.5mm constant amplitude, 8.4Hz to 150Hz, 1G acceleration.