

# VISION430™

Advanced PLC integrated with a 4.3" wide aspect color touchscreen. Includes an onboard I/O configuration; expand up to 512 I/Os

## Features:

### HMI

- 1024 user-designed screens and 250 images per application
- HMI graphs - color-code Trends
- Built-in alarm screens
- Text String Library - easy localization
- Memory and communication monitoring via HMI - No PC needed

### PLC

- I/O options include high-speed, temperature & weight measurement
- Auto-tune PID, up to 24 independent loops
- Recipe programs and datalogging via Data Tables
- Micro SD card - log, backup, clone & more
- Date & Time-based control

### Communication

- TCP/IP via Ethernet
- Web server: Use built-in HTML pages, or design complex pages to view and edit PLC data via the Internet
- Send e-mail function
- SMS messaging
- GPRS/GSM
- Remote Access utilities
- MODBUS protocol support
- CANbus: CANopen, UniCAN, SAE J1939 and more
- DF1 Slave
- SNMP Agent V1
- FB Protocol Utility: enables serial or TCP/IP communications with 3<sup>rd</sup>-party device; barcode readers, frequency converters, etc
- Ports: supplied with mini-USB programming port ; 2 ports may be added: 1 Serial/Ethernet/Profibus and 1 CANbus



V430

“ The huge advantage of this PLC was that - with everything built-in - the communications and use of tags in the HMI was so simple and intuitive. ”

CE/UL

Ashley Parr,  
HPS

| <b>V430</b>  |  |   |   |   |  |  |  |  |  |   |
|--|--|---|---|---|--|--|--|--|--|---|
| Article Number   | V430-J-B1  | V430-J-RH2  | V430-J-R34  | V430-J-TR34   | V430-J-RH6   | V430-J-RA22  | V430-J-TRA22   | V430-J-T2  | V430-J-T38   | V430-J-TA24   |
| No onboard I/Os  | No onboard I/Os  | 10 Digital<br>2 D/A Inputs <sup>1</sup><br>6 Relay Outputs<br>2 High-speed Transistor Outputs | 20 Digital<br>2 D/A Inputs <sup>1</sup><br>12 Relay Outputs | 20 Digital<br>2 D/A Inputs <sup>1</sup><br>8 Relay<br>4 High speed Transistor Outputs | 6 Digital, 2 D/A<br>4 Analog Inputs <sup>1</sup><br>6 Relay Outputs<br>2 High-speed Transistor Outputs | 8 Digital<br>2 D/A,<br>2 PT100/TC/<br>Digital <sup>1</sup> Inputs<br>8 Relay<br>2 Analog Outputs | 8 Digital, 2 D/A<br>2 PT100/TC/<br>Digital <sup>1</sup> Inputs<br>4 Relay, 2 Analog<br>4 High-speed Transistor Outputs | 10 Digital<br>2 D/A Inputs <sup>1</sup><br>12 Transistor Outputs | 20 Digital<br>2 D/A Inputs <sup>1</sup><br>16 Transistor Outputs | 8 Digital<br>2 D/A, 2 PT100/<br>TC/Digital <sup>1</sup> Inputs<br>10 Transistor<br>2 Analog Outputs |
| <b>Inputs</b>  |  |   |   |   |  |  |  |  |  |   |
| Digital pnp/npn  |  | 12  | 22  | 22  | 8  | 12   | 12   | 12   | 22   | 12  |
| HSC/Shaft-Encoder/<br>Max. Freq. Measurer <sup>2&amp;3</sup> |  | 3 200kHz <sup>4</sup><br>32-bit   | 3 30kHz<br>32-bit   | 3 200kHz <sup>4</sup><br>32-bit   | 1 200kHz <sup>4</sup><br>32-bit  | 1 30kHz<br>32-bit  | 1 200kHz <sup>4</sup><br>32-bit  | 3 30kHz<br>32-bit  | 2 30kHz<br>32-bit  | 1 30kHz<br>32-bit   |
| Analog   | None   | 2 10-bit, 0-10V<br>0-20mA<br>4-20mA   | 2 10-bit, 0-10V<br>0-20mA<br>4-20mA                         | 2 10-bit, 0-10V<br>0-20mA<br>4-20mA   | 2 10-bit, 0-10V<br>0-20mA, 4-20mA<br>and 4 10-bit,<br>0-20mA<br>4-20mA                                 | 2 14-bit<br>0-10V,<br>0-20mA<br>4-20mA   | 2 (2 modes)<br>Normal: 14-bit<br>Fast: 12-bit<br>0-10V, 0-20mA<br>4-20mA   | 2 10-bit<br>0-10V<br>0-20mA<br>4-20mA                            | 2 10-bit<br>0-10V,<br>0-20mA<br>4-20mA                           | 2 (2 modes)<br>Normal: 14-bit<br>Fast: 12-bit<br>0-10V,<br>0-20mA,<br>4-20mA<br>and<br>2 PT100/TC   |
| Temperature Measurement                                      |  | None  | None  | None  | None   | and<br>2 PT100/TC  | and<br>2 PT100/TC  | None   | None   | and<br>2 PT100/TC   |
| <b>Outputs</b>   |  |   |   |   |  |  |  |  |  |   |
| Digital  | None   | 6 relay   | 12 relay  | 8 relay   | 6 relay  | 8 relay  | 4 relay  | 12 pnp   | 16 pnp   | 10 pnp  |
| High-Speed Outputs/PWM                                       |  | 2 npn (2 PTO)<br>200kHz max   | None  | 4 npn (3 PTO)<br>200kHz max   | 2 npn (2 PTO)<br>200kHz max  | None   | 4 npn (2 PTO)<br>200kHz max  | 7 0.5kHz   | 7 0.5kHz   | 5 0.5kHz  |
| Analog   |  | None  | None  | None  | None   | 2 12-bit<br>0-10V, 4-20mA  | 2 12-bit<br>0-10V, 4-20mA  | None   | None   | 2 12-bit<br>0-10V, 4-20mA   |
| <b>I/O Expansion</b>   | Local or Remote I/Os may be added via expansion port or via CANbus   |   |   |   |  |  |  |  |  |   |
| <b>Program</b>   | Application Logic: 512K • Images: 12MB • Fonts: 1MB  |   |   |   |  |  |  |  |  |   |
| Application Memory   | 15µ sec per 1K of typical application  |   |   |   |  |  |  |  |  |   |
| Scan Time  | 8192 coils, 4096 registers, 512 long integers (32-bit), 256 double words (32-bit unsigned), 64 floats, 384 timers (32-bit), 32 counters<br>Additional non-retainable operands: 1024 X-bits, 512 X-integers, 256 X-long integers, 64 X-double words |   |   |   |  |  |  |  |  |   |
| Memory Operands  | 120K dynamic RAM data (recipe parameters, datalogs, etc.), up to 256K fixed data   |   |   |   |  |  |  |  |  |   |
| Data Tables  | Store datalogs, Alarm History, Data Tables, Trend data, export to Excel • Back up Ladder, HMI & OS, clone PLCs   |   |   |   |  |  |  |  |  |   |
| SD Card (Micro)  | Trends: graph any value and display on HMI • String Library: instantly switch HMI language   |   |   |   |  |  |  |  |  |   |
| Enhanced Features  | <b>Operator Panel</b>  |   |   |   |  |  |  |  |  |   |
| Type & Colors  | TFT LCD • 65,536 colors, 16-bit resolution • Brightness - Adjustable via touchscreen or software   |   |   |   |  |  |  |  |  |   |
| Display  | Resolution: 480x272 pixels • Size: 4.3"  |   |   |   |  |  |  |  |  |   |
| Touchscreen  | Resistive, Analog  |   |   |   |  |  |  |  |  |   |
| Keys   | 5 programmable keys. Labeling options - function keys, arrows, or customized   |   |   |   |  |  |  |  |  |   |
| <b>General</b>   | 24VDC, except for V430-J-B1, which is 12/24VDC   |   |   |   |  |  |  |  |  |   |
| Power Supply   | 7 years typical at 25°C, battery back-up for all memory sections and RTC   |   |   |   |  |  |  |  |  |   |
| Battery  | Real-time clock functions (date and time)  |   |   |   |  |  |  |  |  |   |
| Clock  | IP66/IP65/NEMA4X (when panel mounted)  |   |   |   |  |  |  |  |  |   |
| Environment  | CE, UL   |   |   |   |  |  |  |  |  |   |
| Standard   | Many of our products are also UL Class 1 Div 2 and GOST certified - please contact Unitronics  |   |   |   |  |  |  |  |  |   |

<sup>1</sup> Adapt specific inputs to function as digital or analog, and in certain models as TC or PT100. This reduces the number of free digital inputs. For example, V350-35-RA22 offers 12 digital inputs. Implementing 2 TC inputs requires 4, leaving 8 free.

<sup>2</sup> Certain inputs can function as high-speed counters, shaft-encoder inputs, or normal digital inputs.

<sup>3</sup> This specification depends on cable length.

<sup>4</sup> This specification depends upon driver type.  
vertrieb@spectra.de

## Order Information

### Item

|            |  |
|------------|--|
| V130-33-B1 | PLC with Classic panel, Monochrome display 2.4"  |
| V130-J-B1  | PLC with Flat panel, Monochrome display 2.4"     |
| V350-35-B1 | PLC with Classic panel, Color touch display 3.5" |
| V350-J-B1  | PLC with Flat panel, Color touch display 3.5"    |
| V430-J-B1  | PLC with Flat panel, Color touch display 4.3"    |

You can find additional information, such as wiring diagrams, in the product's installation guide located in the Technical Library at [www.unitronics.com](http://www.unitronics.com).

## Power Supply

| Item                     | V130-B1<br>V130J-B1                          | V350-B1<br>V350J-B1 | V430J-B1    |
|--------------------------|--|---------------------|-------------|
| Input voltage            | 12VDC or 24VDC                               |                     |             |
| Permissible range        | 10.2VDC to 28.8VDC with less than 10% ripple |                     |             |
| Max. current consumption | See Note 1                                   |                     |             |
| npn inputs               | 200mA@24VDC                                  | 220mA@24VDC         | 220mA@24VDC |
| pnp inputs               | 100mA@24VDC                                  | 110mA@24VDC         | 110mA@24VDC |

### Notes:

- To calculate the actual power consumption, subtract the current for each unused element from the maximum current consumption value according to the values below:

|              | Input voltage | Backlight | Ethernet card |
|--------------|---------------|-----------|---------------|
| V130/J       | 12V           | 20mA      | 70mA          |
| V350/J/V430J |               | 40mA      | 70mA          |
| V130/J       | 24V           | 10mA      | 35mA          |
| V350/J/V430J |               | 20mA      | 35mA          |

## Graphic Display Screen

| Item                      | V130-B1<br>V130J-B1   | V350-B1<br>V350J-B1  | V430J-B1          |
|---------------------------|---|--|-------------------|
| LCD Type                  | STN, LCD display  | TFT, LCD display   | TFT, LCD display  |
| Illumination backlight    | White LED   | White LED  | White LED         |
| Display resolution        | 128x64 pixels   | 320x240 pixels   | 480x272 pixels    |
| Viewing area              | 2.4"  | 3.5"   | 4.3"              |
| Colors                    | Monochrome  | 65,536 (16-bit)  | 65,536 (16-bit)   |
| Screen Contrast           | Via software<br>(Store value to SI 7,<br>values range: 0 to 100%) | Fixed  | Fixed             |
| Touchscreen               | None  | Resistive, analog  | Resistive, analog |
| 'Touch' indication        | None  | Via buzzer   | Via buzzer        |
| Screen brightness control | Via software<br>(Store value to SI 9,<br>0 = Off, 1 = On)         | Via software<br>(Store value to SI 9, values range: 0 to 100%)     |                   |
| Virtual Keypad            | None  | Displays virtual keyboard when the application requires data entry |                   |

## Keypad

| Item           | V130-B1<br>V130J-B1   | V350-B1<br>V350J-B1  | V430J-B1 |
|----------------|---|--|----------|
| Number of keys | 20 keys, including 10 user-labeled keys   | 5 programmable function keys   |          |
| Key type       | Metal dome, sealed membrane switch  |  |          |
| Slides         | Slides may be installed in the operating panel faceplate to custom-label the keys. Refer to <i>V130 Keypad Slides.pdf</i> . A complete set of blank slides is available by separate order | Slides may be installed in the operating panel faceplate to custom-label the keys. Refer to <i>V350 Keypad Slides.pdf</i> . Two sets of slides are supplied with the controller: one set of arrow keys, and one blank set. | None     |

## Program

| Item              | V130-B1<br>V130J-B1 | V350-B1<br>V350J-B1 | V430J-B1 |
|-------------------|---------------------|---------------------|----------|
| Memory size       |                     |                     |          |
| Application Logic | 512KB               | 512KB               | 512KB    |
| Images            | 256KB               | 6MB                 | 12MB     |
| Fonts             | 128KB               | 1MB                 | 1MB      |

| Operand type       | Quantity   |                                     | Symbol | Value                                       |
|--------------------|--|-------------------------------------|--------|---|
| Item               | V130-B1<br>V130J-B1  | V350-B1<br>V350J-B1<br>V430J-B1     |        |   |
| Memory Bits        | 4096   | 8192                                | MB     | Bit (coil)                                  |
| Memory Integers    | 2048   | 4096                                | MI     | 16-bit signed/unsigned                      |
| Long Integers      | 256  | 512                                 | ML     | 32-bit signed/unsigned                      |
| Double Word        | 64   | 256                                 | DW     | 32-bit unsigned                             |
| Memory Floats      | 24   | 64                                  | MF     | 32-bit signed/unsigned                      |
| Fast Bits          | 1024   | 1024                                | XB     | Fast Bits (coil) – not retained             |
| Fast Integers      | 512  | 512                                 | XI     | 16 bit signed/unsigned (fast, not retained) |
| Fast Long Integers | 256  | 256                                 | XL     | 32 bit signed/unsigned (fast, not retained) |
| Fast Double Word   | 64   | 64                                  | XDW    | 32 bit unsigned (fast, not retained)        |
| Timers             | 192  | 384                                 | T      | Res. 10 ms; max 99h, 59 min, 59.99s         |
| Counters           | 24   | 32                                  | C      | 32-bit                                      |
| Data Tables        | 120K dynamic data (recipe parameters, datalogs, etc.)<br>192K fixed data (read-only data, ingredient names, etc)<br>Expandable via SD card. See Removable Memory below |                                     |        |   |
| HMI displays       | Up to 1024   |                                     |        |   |
| Program scan time  | 20µs per 1kb of typical application  | 15µs per 1kb of typical application |        |   |

## Removable Memory

Micro SD card                      Compatible with standard SD and SDHC; up to 32GB store datalogs, Alarms, Trends, Data Tables, backup Ladder, HMI, and OS.  
See Note 2

### Notes:

2. User must format via Unitronics SD tools utility.

---

## Communication Ports

|                        |   |
|------------------------|---|
| Port 1                 | 1 channel, RS232/RS485 and USB device (V430 only). See Note 3 |
| Galvanic isolation     | No  |
| Baud rate              | 300 to 115200 bps   |
| RS232                  |   |
| Input voltage          | ±20VDC absolute maximum                                       |
| Cable length           | 15m maximum (50')   |
| RS485                  |   |
| Input voltage          | -7 to +12VDC differential maximum                             |
| Cable type             | Shielded twisted pair, in compliance with EIA 485             |
| Cable length           | 1200m maximum (4000')   |
| Nodes                  | Up to 32  |
| USB device (V430 only) |   |
| Port type              | Mini-B, See Note 5  |
| Specification          | USB 2.0 compliant; full speed                                 |
| Cable                  | USB 2.0 compliant; up to 3m                                   |
| Port 2 (optional)      | See Note 4  |
| CANbus (optional)      | See Note 4  |

### Notes:

3. This model is supplied with a serial port: RS232/RS485 (Port 1). The standard is set to either RS232 or RS485 according to jumper settings. Refer to the product's Installation Guide.
4. The user may order and install one or both of the following modules:
  - An additional port (Port 2). Available port types: RS232/RS485 isolated/non-isolated, Ethernet
  - A CANbus portPort module documentation is available on the Unitronics website.
5. Note that physically connecting a PC to the controller via USB suspends RS232/RS485 communications via Port 1. When the PC is disconnected, RS232/RS485 resumes.

---

## I/O Expansion

|        |   |
|--------|---|
|        | Additional I/Os may be added. Configurations vary according to module.<br>Supports digital, high-speed, analog, weight and temperature measurement I/Os.  |
| Local  | Via I/O Expansion Port. Integrate up to 8 I/O Expansion Modules comprising up to 128 additional I/Os. Adapter required (P.N. EX-A2X).   |
| Remote | Via CANbus port. Connect up to 60 adapters to a distance of 1000 meters from controller; and up to 8 I/O expansion modules to each adapter (up to a total of 512 I/Os). Adapter required (P.N. EX-RC1). |

---

## Miscellaneous

|                     |  |
|---------------------|--|
| Clock (RTC)         | Real-time clock functions (date and time)  |
| Battery back-up     | 7 years typical at 25 °C, battery back-up for RTC and system data, including variable data |
| Battery replacement | Yes. Coin-type 3V, lithium battery, CR2450   |

## Dimensions

| Item   |        | V130-B1  | V350-B1  | V430J-B1   |
|--------|--------|--|--|--|
|        |        | V130J-B1   | V350J-B1   |  |
| Size   | Vxxx   | 109 x 114.1 x 68mm<br>(4.29 x 4.49 x 2.67").<br>See Note 6 | 109 x 114.1 x 68mm<br>(4.29 x 4.49 x 2.67").<br>See Note 6 |  |
|        | Vxxx-J | 109 x 114.1 x 66mm<br>(4.92 x 4.49 x 2.59").<br>See Note 6 | 109 x 114.1 x 66mm<br>(4.92 x 4.49 x 2.59").<br>See Note 6 | 136 x 105.1 x 61.3mm<br>(5.35 x 4.13 x 2.41").<br>See Note 6 |
| Weight |        | 255g (9 oz)  | 270g (9.5 oz)  | 300g (10.5 oz)   |

### Notes:

- For exact dimensions, refer to the product's Installation Guide.

## Environment

|                         |  |
|-------------------------|--|
| Operational temperature | 0 to 50°C (32 to 122°F)  |
| Storage temperature     | -20 to 60°C (-4 to 140°F)  |
| Relative Humidity (RH)  | 10% to 95% (non-condensing)  |
| Mounting method         | Panel mounted (IP65/66/NEMA4X)<br>DIN-rail mounted (IP20/NEMA1)                            |
| Operating Altitude      | 2000m (6562 ft)  |
| Shock                   | IEC 60068-2-27, 15G, 11 ms duration  |
| Vibration               | IEC 60068-2-6, 5Hz to 8.4Hz, 3.5mm constant amplitude,<br>8.4Hz to 150Hz, 1G acceleration. |

The information in this document reflects products at the date of printing. Unitronics reserves the right, subject to all applicable laws, at any time, at its sole discretion, and without notice, to discontinue or change the features, designs, materials and other specifications of its products, and to either permanently or temporarily withdraw any of the forgoing from the market.

All information in this document is provided "as is" without warranty of any kind, either expressed or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement. Unitronics assumes no responsibility for errors or omissions in the information presented in this document. In no event shall Unitronics be liable for any special, incidental, indirect or consequential damages of any kind, or any damages whatsoever arising out of or in connection with the use or performance of this information.

The tradenames, trademarks, logos and service marks presented in this document, including their design, are the property of Unitronics (1989) (R"G) Ltd. or other third parties and you are not permitted to use them without the prior written consent of Unitronics or such third party as may own them.

DOC13043-A5 01/15